

Glass/Body Primer

Art.: 02.0441.0000

Jar 30 ml

Glass/Body Primer is a black UV resistant primer that can be used for repairing damage to the ceramic edge of windscreens or for retouching damaged window rabbets to which the windscreen sealant will have to adhere. Moreover it is suited for both optical and protective applications, especially at places where UV protection is required.



Base:	Butane, butyl acetate and polyurethane
Density:	980 kg/m ³
Consistency:	Liquid
Viscosity:	± 10-15 mPa.s
Solvents:	Butane and butyl acetate
Flash point:	< 0°C
Temperature resistance:	-30°C to +100°C
Percentage of solids:	± 35%
Application conditions:	+10°C to +30°C
Type of surface:	Glass, ceramic edge of vehicle windscreens and painted surface
Surface preparation:	The surface must be clean, dry and free of grease. Cut away the old sealant layer up to a thickness of ± 2 mm. Clean the edge of the windscreen with Innotec Multisol .
Application method:	Shake the jar well before use. Apply Glass/Body Primer with a cotton wool to the ceramic edge of the windscreen. Treat any damage to the rebate with Glass/Body Primer. If there are no remains of old sealant in the rebate, clean with Innotec Multisol and treat with Glass/Body Primer. Allow to dry for at least 10 minutes.
Open time:	± 30 minutes
Drying time:	± 10 minutes
Recommended layer thickness:	Even, covering layer
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	9 months in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
Other details:	Glass/Body Primer has good UV resistance combined with a ceramic edge of vehicle





windcreens.

EAN Code: 5400563008027

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

