

Black Body-Paint

Art.: 02.3130.5000

Aerosol can 500 ml

Black Body-Paint is a perfect mat black paint with a low chalk percentage, as a result of which the product does not weather for a long time and is extremely resistant to the effects of weather. Black Body-Paint is also very impact and chip resistant and therefore extremely suited for spraying OEM mat black body parts. It is easy to sand, so ideal as a control spray.



Base:	Cellulose paint
Density:	773 kg/m ³
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Mixture of aromatic and aliphatic solvents
Flash point:	< 0°C
Temperature resistance:	-20°C to +125°C
UV resistance:	Good
Water resistance:	Excellent
Solvent resistance:	Moderate
Application conditions:	+15°C to +25°C (65% relative humidity)
Type of surface:	Almost all modern plastics and metals. Not suitable for plastics containing styrene.
Surface preparation:	The surface must be clean, dry and free of dust and grease. Sand the surface, preferably with a sanding block. Clean metal surfaces with Innotec Multisol or Innotec Seal and Bond Remover . Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic and treat with Innotec Repaplast Primer New Formula .
Application method:	Shake spray can well before use. Spraying distance ± 20 cm. Apply in a criss-cross layer. When applying several layers leave 10 minutes for the product to evaporate between each layer. After use, invert can and spray until clear to clean the nozzle.
Dust dry:	± 10 minutes (at 20°C / 65% relative humidity)
Curing time:	2 hours (at 20°C / 65% relative humidity)
Recommended layer thickness:	± 85µ (wet), ± 20µ (dry)
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry





Type of batchcode:	F
Other details:	If Black Body-Paint is used as a control layer when sanding, a drying time of 2-3 minutes will be sufficient.
EAN Code:	5400563010860

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

