

Construction Primer White

Art.: 02.0400.0100

Aerosol can 500 ml

Construction Primer is a single component primer specially developed for the simple but professional priming of various surfaces. Construction Primer adheres perfectly to just about any type of surface such as metal, wood, and old layers of lacquer.



Base:	Nitro
Density:	820 kg/m ³
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Mixture of aromatic and aliphatic solvents
Flash point:	< 0°C
Temperature resistance:	-20°C to +110°C
Water resistance:	Good
Solvent resistance:	Good
Application conditions:	+15°C to +30°C
Type of surface:	Ferrous and non-ferrous metal, galvanized steel, wood and sanded old paint layers
Surface preparation:	The surface must be clean, dry and free of dust and grease. Sand the surface and clean with Innotec Multisol . Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic and pre-treat them with Innotec Repaplast Primer New Formula .
Application method:	Shake spray can well before use. Spraying distance 25 cm. Apply in several thin criss-cross layers. When applying several layers leave 5 minutes for the product to evaporate in between. After use, invert can and spray until clear to clean the nozzle.
Dust dry:	± 5 minutes (at 20°C / 65% relative humidity)
Curing time:	60 minutes (at 20°C / 30µ layer thickness)
Recommended layer thickness:	30µ
Sandability:	After ± 15 minutes (at 20°C)
Paintability:	After ± 20 minutes (at 20°C), with almost all modern paint systems. Due to the huge variety of paint types on the market, it is best to test the paint beforehand.
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging





Storage conditions: Store cool and dry

Type of batchcode: F

Other details: OEM approved

EAN Code: 5400563006962

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

